

### Declaration of Performance

(according to regulation EU No 305/2011)

DoP No. 00186217 05 2016

1) Code of the product type: 1.0045, 1.0577, 1.0596 according to EN 10027-2

2) Type: coils (+AR, + M) **S355 JR, J2, K2** according to EN 10025-2-2004

Intended use of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

To be used in welded, bolted and riveted structures

3) PAO Severstal

162608, Russia, Vologda region, Cherepovets, Mira str., 30

System of assessment and verification of constancy of performance of the product: System 2+ (according to certificate)

Notified factory production control certification body No. 0038 LRV performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment, and evaluation of factory production control and issued the certificate of conformity of the factory production control № 0038/CPR/RQA/666869/1

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in the table.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by

Technical Development  
and Quality Director

Mishnev P.A.

Date: « 11 » АПР 2016.

STAMP HERE



Russian steel branch  
Cherepovets  
JSC "Severstal Management"

30, Mira street  
Cherepovets  
Vologda region  
Russia, 162608

T: +7 (8202) 53-09 00  
F: +7 (8202) 53-09-15  
severstalm@severstal.com  
www.severstal.com



П.А. МИШНЕВ



Essential characteristic		Performance	Harmonised technic specification
Tolerances on dimension and shape	Sheet / coil	EN 10048, EN 10051, EN 10029	EN 10025-2 2004
	Nominal thickness, (mm)	Values, (MPa)	
Yield strength	≤ 16	355	
	> 16 ≤ 24	345	
Tensile strength	Nominal thickness, (mm)	Values, (MPa)	
	< 3	510 - 680	
Elongation	≥ 3 ≤ 24	470 - 630	
	Nominal thickness, (mm)	Values, (%)	
	≤ 1	14	
	> 1 ≤ 1,5	15	
	> 1,5 ≤ 2	16	
	> 2 ≤ 2,5	17	
Impact strength (-20 °C)	> 2,5 ≤ 3	18	
	> 3 ≤ 24	22	
Equivalent carbon content (weldability)	Nominal thickness, (mm)	Values, (J)	
	≤ 24	27	
Durability (chemical composition)	Nominal thickness, (mm)	Values, (%)	
	≤ 24	C : 0,22; Si : 0,55; Mn : 1,60; P : 0,025; S : 0,025; Cu : 0,55	