

Declaration of Performance

(according to regulation EU No 305/2011)

DoP No. 00186217-06-2016

1) Code of the product type: 1.056 according to EN 10027 2

2) Type: sheets (+ N) S355 NL according to EN 10025-3-2004

Intended use of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

To be used in welded, bolted and riveted structures

3) PAO Severstal

162608, Russia, Vologda region, Cherepovets, Mira str., 30

System of assessment and verification of constancy of performance of the product: System 2+ (according to certificate)

Notified factory production control certification body No 0038 LRV performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment, and evaluation of factory production control and issued the certificate of conformity of the factory production control № 0038/CPR/RQA/666869/1.

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in the table

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:




Mishnev P.A.

STAMP HERE

Russian steel branch
Cherepovets
JSC "Severstal Management"

30, Mira street
Cherepovets
Vologda region
Russia, 162608

T: +7 (8202) 53-09-00
F: +7 (8202) 53-09-15
severstalm@severstal.com
www.severstal.com



Essential characteristic		Performance	Harmonised technical specification
Tolerances on dimension and shape	Sheet	EN 10048, EN 10051, EN 10029	
Yield strength	Nominal thickness, (mm)	Values, (MPa)	
	≤ 16	355	
	> 16 ≤ 40	345	
	> 40 ≤ 63	335	
Tensile strength	> 63 ≤ 80	326	
	Nominal thickness, (mm)	Values, (MPa)	
Elongation	≤ 80	470 + 630	
	Nominal thickness, (mm)	Values, (%)	
	≤ 16	22	
	> 16 ≤ 40		
> 40 ≤ 63			
Impact strength (-20 °C)	> 63 ≤ 80	21	
	Nominal thickness, (mm)	Values, (J)	
	≤ 63	27	
> 63 ≤ 80			
Equivalent carbon content (weldability)	Nominal thickness, (mm)	Values, (%)	
	≤ 63	0,43	
	> 63 ≤ 80	0,45	
Durability (chemical composition)	Nominal thickness, (mm)	Values, (%)	
	≤ 63	C : 0,18; Si : 0,50; Mn : 0,90 - 1,65; P : 0,025; S : 0,020; Cu : 0,55	
	> 63 ≤ 80		